Amendments to the Claims

The following listing of claims will replace all prior versions, and listings,

of claims in the ancestor application.

1. (Currently Amended) A processor, comprising:

a decoder to implement a first and second flow synonym for a first

instruction, said decoder to associate select at least one of said first and

second flow synonym with said for decoding said first instruction; and

a scheduler to schedule said selected at least one of said first and

second flow synonym for execution.

2. (Original) The processor of claim 1, wherein said first flow

synonym is to execute on a first execution unit and said second flow

synonym is to execute on a second execution unit.

3. (Original) The processor of claim 2, wherein said first execution

unit and said second execution unit are of differing types.

4. (Original) The processor of claim 2, wherein said first execution

unit and said second execution unit are of differing precisions.

5. (Original) The processor of claim 1, wherein said first flow

synonym and said second flow synonym are to execute on a common

execution unit.

Application No.: 10/733,014 Filed: December 10, 2003

Examiner: William M. Treat

6. (Currently Amended) The processor of claim 1, wherein said

decoder is to make said association selection based upon processor

status.

7. (Currently Amended) The processor of claim 1, wherein said

decoder is to make said association selection based upon a rule.

8. (Original) The processor of claim 7, wherein said rule considers

a power configuration of said processor.

9. (Original) The processor of claim 7, wherein said rule considers

failure status of an execution unit.

10. (Cancelled)

11. (Currently Amended) The processor of elaim 10 claim 1,

further comprising a retirement module to retire whichever said first or

said second flow synonym first completes execution, if both said first

and second flow synonyms are scheduled for execution.

12. (Currently Amended) The processor of elaim 10 claim 1,

further comprising a retirement module to compare execution results of

said first and said second flow synonym and raise an exception upon

mismatch, if both said first and second flow synonyms are scheduled

for execution by different execution units.

Application No.: 10/733,014 Filed: December 10, 2003

Examiner: William M. Treat Art Unit: 2181 13. (Original) A method, comprising:

determining whether each of a plurality of execution units is

available; and

if a first one of said plurality of execution units is available, then

choosing a first flow synonym corresponding to said first available

execution unit and further scheduling said first flow synonym for

execution on said first available execution unit.

14. (Original) The method of claim 13, further comprising if none

of said plurality of execution units is available, then arbitrating to select

a second flow synonym from a plurality of flow synonyms.

15. (Original) The method of claim 13, further comprising if more

than one of said plurality of execution units is available, then choosing

said first flow synonym from a plurality of flow synonyms corresponding

to one of said available execution units based upon system performance

rules.

16. (Original) The method of claim 13, wherein said determining

includes reading a processor status register.

17. (Original) The method of claim 16, wherein said processor

status register indicates a second one of said execution units is less

available due to a fault in said second one of said execution units.

Application No.: 10/733,014 Filed: December 10. 2003

18. (Original) The method of claim 16, wherein said processor status register indicates a second one of said execution units is available due to a processor reduced power mode.

19. (Original) A method, comprising:

decoding an instruction into a first flow synonym and a second flow synonym;

scheduling said first flow synonym and said second flow synonym for execution on a first execution unit and a second execution unit; executing said first flow synonym on said first execution unit; and executing said second flow synonym on said second execution unit.

- 20. (Original) The method of claim 19, further comprising retiring said first flow synonym when said first flow synonym finishes execution before said second flow synonym finishes execution.
- 21. (Currently Amended) The system method of claim 19, further comprising raising an exception when a first execution result of said first flow synonym does not equal a second execution result of said second flow synonym.

Application No.: 10/733,014 Filed: December 10, 2003

22. (Currently Amended) A system, comprising:

a processor including a decoder to implement a first and second flow synonym for a first instruction, said decoder to associate select at least one of said first and second flow synonym with said for decoding said first instruction, and a scheduler to schedule said selected at least one of said first and second flow synonym for execution;

an interface to couple said processor to input/output circuitry;

an audio input/output circuitry coupled to said interface.

23. (Original) The system of claim 22, wherein said first flow synonym is to execute on a first execution unit and said second flow synonym is to execute on a second execution unit.

24. (Original) The system of claim 23, wherein said first execution unit and said second execution unit are of differing types.

25. (Original) The system of claim 23, wherein said first execution unit and said second execution unit are of differing precisions.

26. (Original) The system of claim 22, wherein said first flow synonym and said second flow synonym are to execute on a common execution unit.

27. (Currently Amended) The system of claim 22, wherein said decoder is to make said association selection based upon processor status.

Application No.: 10/733,014 Filed: December 10, 2003

28. (Currently Amended) The system of claim 22, wherein said decoder is to make said association selection based upon a rule.

29. (Original) The system of claim 28, wherein said rule considers a power configuration of said processor.

30. (Original) The system of claim 28, wherein said rule considers failure status of an execution unit.

31. (Cancelled)

32. (Currently Amended) The system of elaim 31 claim 22, further comprising a retirement module to retire whichever said first or said second flow synonym first completes execution, if both said first and second flow synonyms are scheduled for execution.

33. (Currently Amended) The system of elaim 31 claim 22, further comprising a retirement module to compare execution results of said first and said second flow synonym and raise an exception upon mismatch, if both said first and second flow synonyms are scheduled for execution by different execution units.

34. (Original) A processor, comprising:

means for determining whether each of a plurality of execution units is available; and

if said means for determining determines that a first one of said plurality of execution units is available, then means for choosing a first

Application No.: 10/733,014 Filed: December 10, 2003

flow synonym corresponding to said first available execution unit and further means for scheduling said first flow synonym for execution on

said first available execution unit.

35. (Original) The processor of claim 34, further comprising if said

means for determining determines that none of said plurality of

execution units is available, then means for arbitrating to select a

second flow synonym from a plurality of flow synonyms.

36. (Original) The processor of claim 34, further comprising if said

means for determining determines that more than one of said plurality

of execution units is available, then means for choosing said first flow

synonym from a plurality of flow synonyms corresponding to one of said

available execution units based upon system performance rules.

37. (Original) The processor of claim 34, wherein said means for

determining includes means for reading a processor status register.

38. (Original) The processor of claim 37, wherein said processor

status register indicates a second one of said execution units is less

available due to a fault in said second one of said execution units.

39. (Original) The processor of claim 37, wherein said processor

status register indicates a second one of said execution units is

available due to a processor reduced power mode.

Application No.: 10/733,014 Filed: December 10, 2003

Examiner: William M. Treat Art Unit: 2181 40. (Original) A processor, comprising:

means for decoding an instruction into a first flow synonym and a second flow synonym;

means for scheduling said first flow synonym and said second flow synonym for execution on a first execution unit and a second execution unit;

means for executing said first flow synonym on said first execution unit;

means for executing said second flow synonym on said second execution unit.

- 41. (Original) The processor of claim 40, further comprising means for retiring said first flow synonym when said first flow synonym finishes execution before said second flow synonym finishes execution.
- 42. (Original) The processor of claim 40, further comprising means for raising an exception when a first execution result of said first flow synonym does not equal a second execution result of said second flow synonym.

Application No.: 10/733,014 Filed: December 10, 2003